

Very Narrow Aisle Forklift

Used Very Narrow Aisle Forklift Arkansas - Warehousing needs greatly focus on space-saving techniques and layout to maximize expensive square footage and decrease travel time needed to get goods from the loading docks and from point A to point B. Narrow aisles need specific solutions to allow goods to be accessed and stored properly. More space can be given to storage as less space is needed for accessing the aisle. These warehouse configurations are often referred to as warehouse optimization. Warehouse Optimization Implementing very narrow aisle warehouse optimization is a huge benefit of warehouse optimization. One of the most important benefits is the increased storage space. Since very narrow forklift trucks have been designed to take up significantly less space, warehouse aisle widths can be reduced to half the width needed by traditional forklifts. Many very narrow aisle forklifts offer greater stack height capability which further increases the storage capacity per square foot. Costs can be drastically decreased with a narrow aisle forklift compared to a standard aisle configuration as less warehouse space is required for the same quantity of stock. In most urban areas where square footage is very costly, this is a huge benefit to warehouse operations. When planned carefully and properly, it is possible to increase warehouse storage area by up to 80 percent by implementing a very narrow aisle width configuration. This warehouse design creates more rack faces and increased product access. Since greater quantities of products are situated in a more accessible area, there is less travel time needed for gathering and storing items. Warehouse layouts usually utilize a narrow aisle or very narrow aisle plan. Narrow aisles are usually those that use less than 11 feet of aisle width. Very narrow aisles reduce the aisle width further to around six-and-a-half feet. Both of these aisle widths provide significantly increased storage opportunities. However, they also create challenges when turning within the aisles using forklifts for stocking and order picking. A variety of very narrow forklifts have been designed to easily maneuver in narrow aisles. It is necessary to know the dimensions of the aisle when selecting a forklift for a certain job. Having the right aisle dimensions will save money and time instead of purchasing the wrong forklift that won't be able to conquer the applications. It is essential to take any columns, posts or utilities into account before deciding a type of narrow aisle forklift design as these can block access. Very Narrow Aisle Forklift Trucks Rechargeable batteries are typical for powering very narrow aisle forklift trucks and most models are electric. Stand-up riders are a popular design for very narrow aisle forklift trucks. There are different very narrow aisle forklift designs such as order pickers, reach trucks, wing-mast or turret and end-control riders. Reach Forklift Trucks Developed as a kind of rider stacker forklift, the reach forklift trucks can be configured for narrow aisle locations. This machine earned its name by its ability to reach its forks to secure a load. The two kinds of reach trucks the moving carriage and the moving mast. The moving carriage works by raising and lowering the carriage, along with the operator. The moving mast works by raising and lowering the forks along the mast, while the operator stays at ground level. Of the two kinds of reach trucks, the moving mast reach truck is the safer of the two varieties. Reach trucks use a pantograph system, a type of jointed framework, which allows the operator to reach for or place a load without the need to move the forklift itself. Order Pickers Order pickers were created to specifically pick orders from difficult-to-access racks. These machines are used for picking up lighter stock that can be moved by hand. These order pickers work by lifting the operator up to the level of goods in order to identify and pick the specific item or items necessary to fill an order. End-Control Riders End-control riders are used to pick loads located at floor level and transport the load horizontally, rather than lift or lower loads from various heights. Turret or Swing-Mast Forklift Turret or swing-mast very narrow aisle forklift have a pivoting articulating swivel mast. The mast swivels to enable pallets to be positioned on the right or left side of the forklift. Guided Very Narrow Aisle Trucks Many very narrow aisle forklift trucks are able to be guided down aisles by wire or rail. Since the forklift truck is guided, the chance of colliding with racks while traversing down the aisles is very low. In rail-guided models, sets of rails are placed into the floor on each

side of the aisle. They run the length of the aisle and also curve around the aisles' edge. The forklift is fitted with special wheel guides that slide into the rails, preventing the forklift from moving outside the rail guards. Wire-guidance forklift systems install wires on the floor instead of rails and the wires run down the middle of the aisle. The wire-guides function similarly to the rail systems except the forklift has a wire-guide system to prevent the machine from traveling where it is not supposed to.

Work Site Considerations To use a narrow aisle configuration, there are some key considerations that need to be made. The floor and the rack construction needs to be evaluated to avoid any issues since the very narrow aisle units have extremely high racking systems. There are four areas which must be meticulously prepared before setting up a racking system and must be continuously monitored and maintained throughout the operation of the warehousing system:

1. The floor must be level;
2. Cracks must be repaired;
3. Load capacity of floor must be appropriate;
- and 4. The racks must be plumb.

Level Floor Because of the height of the racking systems, any slight slope of the floor is likely to negatively affect the plumbness of the racks, especially over time when loads are continuously placed and removed on the racks. A level floor is vital for the safety and integrity of the operator, employees, stock and the warehouse.

Crack Repair Cracks in the floor ideally should be fixed once they are noticed to ensure everyone's safety. The level of the floor can become unstable with cracks when they are only 3/8 inches wide. They will need to be filled properly with material as hard as the rest of the floor.

Floor Load Capacity The floor needs to meet specific minimum requirements prior to a narrow aisle configuration. The floor should have three thousand psi concrete minimum and contain evenly distributed rebar at three to four inches under the surface. Depending on the load requirements and configuration, additional reinforcements may be needed.

Plumb Racks Installing the racks safely and correctly is vital for the entire system. There is a major chance of rack failure if improper installation occurs. One of the most important details to ensure proper installation, is that all racks are plumb. Rack shims can help the rack stay plumb to one inch at the height of thirty feet. Racking failure can happen if the aforementioned measures are not taken or implemented correctly. Racking failure can kill or injure employees, damage equipment and result in horrible damage. Because of these reasons, these measures are the most important part of implementing a narrow aisle configuration for warehousing optimization.